

SELECT

range

Technical Information

Composition:	100% filament polyester, multi-coated with microporous polymers and flame retardant
Weight:	370g/m ² (nominal)
Roll width:	145cm (nominal)
Roll length:	50m (nominal)
Flame retardancy:	BS EN1021-1:1994 (Ignition Source - Smouldering Cigarette) BS EN1021-2:1994 (Ignition Source - Match Equivalent) BS5852:1990 Section 4: Ignition Source 5 (Wood Crib) BS7176:1995 Medium Hazard (Crib 5)
Waterproof:	Hydrostatic head BS 3424:1990 > 1 metre
Breathable:	Moisture vapour permeable BS 3546:2001 65%
Martindale abrasion:	End point > 50,000 No pilling
Colour change:	BS 5690:1991 as modified by Annex F of BS 2543:1995 (Severe Contract)
Tear strength:	BS 4303:1968 (1995) (Severe Contract)
Urea resistance:	BS 3424-19:1989 - No deterioration after 24 hours
Flex test:	BS 4818:1993 - No change after Urea soak and 5,000 flexes
Anti-bacterial / Anti-fungal:	Will not support microbial growth (EGIS Microbe Shield®)

Availability:

The complete range of **SELECT** and **KIDZ** fabrics available exclusively from:

CTP
TEXTILES

Covering your creations

CTP Textiles Limited
Unit D4, New Yatt Business Centre, New Yatt
Witney, Oxfordshire, OX29 6TJ
Tel. 0845 4089414
Fax 0845 4089415
email: sales@cptextiles.co.uk
website: www.cptextiles.co.uk